



Features

- Most cost-effective rackmount chassis
- Supports PS/2 single power supply
- Easy-to-install front-accessible drive bays hold 3 x 5.25" and 2 x 3.5" drives (1 x front-accessible and 1 x internal)
- Front-accessible USB and PS/2 interfaces

Specifications

Front I/O	USB	2	
	PS/2	1	
Drive Bay		External	Internal
	5.25"	3	-
	3.5"	1	1*
Cooling	Fan	1 (12 cm/77 CFM)	
	Air Filter	Yes	
Physical Characteristics	Dimensions (W x H x D)	481 x 175 x 446 mm (19 x 7 x 17.6")	
	Weight	10.7 kg (23.5 lb)	
Miscellaneous	LED Indicators	Power and HDD activity	
	Rear Panel	Motherboard version: 1 x 9-pin D-Sub and 1 x 68-pin SCSI openings	
Environment		Operating	Non-Operating
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	-20 ~ 60 °C (-4 ~ 140 °F)
	Humidity	10 ~ 85% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms	2 G

Ordering Information

iRL-410

4U-19" Rackmount Chassis for ATX & uATX MB with Front-Accessible USB and PS/2