



Features

- 4U rackmount chassis supports up to 15 add-on cards
- Shock-resistant disk drive bay design holds up to three 5.25" and one 3.5" disk drives
- Front accessible USB & PS/2 interfaces for easy data transfer
- Dual front-accessible filtered cooling fans provide optimized and streamlined airflow
- Front LEDs indicate power status, and HDD activity
- Lockable front door prevents unauthorized access
- Supports 80 plus single power supply or redundant power supply up to 500W

Specifications

| | | |
|--------------------------|---|----------------------------------|
| Front I/O | External | |
| | 2 | |
| Drive Bay | 1 | |
| | 3 1* | |
| Cooling | 2 (12 cm / 82 CFM each) | |
| | Yes | |
| Physical Characteristics | 482 x 177 x 479 mm (19" x 7" x 18.9") | |
| | 15 kg (33 lb) | |
| Miscellaneous | Power, HDD, and power voltage status | |
| | Backplane version: One 9-pin D-Sub opening | |
| | Motherboard version: Five 9-pin D-Sub & one 25-pin D-sub openings | |
| Environment | Operating | Non-Operating |
| | 0 ~ 40 °C (32 ~ 104 °F) | -20 ~ 60 °C (-4 ~ 140 °F) |
| | 10 ~ 85% @ 40 °C, non-condensing | 10 ~ 95% @ 40 °C, non-condensing |
| | 1 Grms | 2 G |
| | 482 x 177 x 479 mm (19" x 7" x 18.9") | |
| | 15kg (33 lb) | |

Ordering Information

iRL-420

4U-19" Rackmount Chassis for ATX, mATX MB & PICMG 1.0 & 1.3 SBC with Visual Alarm Notification