

Intel® SKL/KBL-S CPU, 2xLAN, VGA+HDMI+DVI, 6xCOM, 4xUSB3.0, 5xUSB2.0, 4xPCIe/PCI, 4xSATA Bay, 4U rackmount, ATX power



Features

- Intel gen 6/7th SKL/KBL-S LGA1151 CPU+H110 PCH
- Dual channel 2xDDR4 2133/2400MHz UDIMM, up to32GB
- Intel 9th HD Graphic, VGA+HDMI+DVI-D 3 display
- 1xI219LM Gig. Ethernet+1xI211AT Gig. Ethernet
- 4xUSB3.0, 5xUSB2.0 (two front and one built-in), Audio out and Mic
- 2xRS232/422/485, 4xRS232, optional 1xLPT or 8 bit DIO
- 1xPCIeX16+1xPCI+2xPCIeX4, 1xFull size Mini PCIe
- 4x3.5 "SATA3.0 shock resistant and anti-vibrationhard disk bay
- Standard 19"4U rackmount chassis with high efficiency air cooling design
- Standard PS2 ATX power supply, 300/500/750W

Specifications

Front I/O	2xUSB2.0(Type A)	
Drive Bay	4	
Cooling	Linear airflow design, front 12025 ball bearing fan, optional 2 rear 8025 ball bearing fan Yes (Optional)	
Environment	Operating	Non-operating
	0~50°C	-40°C~85°C
	10~95%@40°C, Non-condensing	10~95%@40°C, Non-condensing
Miscellaneous	Power Button, Reset Button, Power LED, HDD LED, on board with USB Power jumper 2xLAN(RJ45); 1xHDMI+1xVGA+1xDVI-D; 1xLine out+1xMic 2x3.5mm phone jack	
Physical Characteristics	430x470x173mm	
	14 kg	

Ordering Information

iRL-430	4U-19" Rackmount Chassis for ATX & uATX MB with Front-Accessible USB and PS/2
---------	---