

Intel® SKL/KBL-S CPU, 2xLAN, VGA+HDMI+DVI, 3xCOM, 4xUSB3.0, 5xUSB2.0, 4xPCIe/PCI, 1x3.5"+2x2.5" SATA bay, 4-slot wall mounted, 1U power supply



Features

- Intel 6/7代SKL/KBL-S LGA1151 CPU+H110 PCH
- Dual channel 2xDDR4 2133/2400MHz UDIMM, up to 32GB
- Intel 9th HD Graphic, VGA+HDMI+DVI-D 3 display
- 1xI219LM Gig. Ethernet+1xI211AT Gig. Ethernet
- 4xUSB3.0, 5xUSB2.0 (two front and one built-in), Audio out and Mic
- 2xRS232/422/485, 1xRS232, optional 1xLPT or 8 bit DIO
- 1xPCIeX16+1xPCI+2xPCIeX4, 1xFull size Mini PCIe
- 1x3.5"+2x2.5" SATA3.0 shock resistant and antivibration hard disk bay
- 4-slot wall mounted chassis, standard 1U Flex power supply, optional for different powers

Specifications

Front I/O	2xUSB2.0(Type A)	
	-	
Drive Bay	-	
	1	
Cooling	Front two 9025B fans	
	No	
Environment	Operating	Non-operating
	0~50% (35W-65W CPU)	-40°C~85°C
	10~95%@40°C, Non-condensing	10~95%@40°C, Non-condensing
	-	
Miscellaneous	Power Button, Reset Button, Power LED, HDD LED, on board with USB Power jumper	
	2xLAN(RJ45); 1xHDMI+1xVGA+1xDVI-D; 1xLine out+1xMic 2x3.5mm phone jack	
Physical Characteristics	270x168x331.2mm	
	6.3 kg	

Ordering Information

iRL-713	Wallmount Chassis for ATX/uATX/Mini ITX Motherboard
---------	---